



Coils ESC and Cable Assemblies

Standards

- ASC Coils and cable assemblies conform to Low Voltage Directive

| Type | Part No. | Voltage | Power Input | Electr. Connection | Protection |
|-----------------------|-----------------|---------|-------------|--------------------------------------|--|
| ESC 230V / 50 (60) Hz | 801031 | AC | 8 W | without plug see cable assemblies | IP65 with plug / cable as- sembly |
| ESC 120V / 50 (60) Hz | 801032 | | | | |
| ESC 24V / 50 (60) Hz | 801033 | | | | |
| ESC 24V DC | 801030 | DC | 15 W | | |
| DS2-N15 + ESC 24VAC | 804620 + 801033 | DC | 3 W | with plug and cable assembly | IP65 |

Note: Coils are delivered with retainer kit.
Please order cable assemblies separately.



ESC

Cable Assemblies for ESC Coils

| Type | Part No. | Temperature Range | Cable Length | Wire Diameter | Connector Type |
|---------|----------|--|--------------|--------------------------|----------------|
| ASC-N15 | 804 570 | -50 .. +80°C for stationary use only | 1.5m | 3 x 0.75 mm ² | loose wires |
| ASC-N30 | 804 571 | | 3.0m | | |
| ASC-N60 | 804 572 | | 6.0m | | |



ESC-N15

Cable Assembly With 24V DC Chopper Plug

- Enables standard 24V AC Coil to be used for DC applications
- Low power assumption (3W only)
- No MOPD degradation

| Type | Part No. | Temperature Range | Cable Length | Wire Diameter | Connector Type |
|---------|----------|-------------------|--------------|--------------------------|----------------|
| DS2-N15 | 804 620 | -25 .. +80°C | 1.5 m | 2 x 0.75 mm ² | loose wires |



D2-N15

Other Accessories for Solenoid Valves

| Type | Part No. | Description |
|-----------|----------|--|
| X 11981-1 | 027 451 | Service tool for 110RB. 240RA. 540RA. 3031 |
| ESC-K01 | 801 034 | Coil clip |
| PG9 Plug | 801 012 | Plug according to EN 175301 with cable gland PG 9 |
| PG11 Plug | 801 013 | Plug according to EN 175301 with cable gland PG 11 |