

## 3-Way Solenoid Valves Series M36

### Features

- For heat reclaim application
- Pilot connection to suction line required. no minimum pressure drop
- Compact size
- No disassembly necessary for brazing
- Max. allowable pressure PS: 35 bar

### Accessories

- Actuation coil and cable assemblies available for various voltages, see 'Coils ESC and Cable Assemblies



M36-118



M36-078 with ESC Coil and DS2 Chopper Plug

### Capacity Data

Type	Part No.	Connection Solder/ODF		Nominal Capacity Q <sub>n</sub> (kW)				kv-Value m <sub>3</sub> /h	Coil Type
		mm	Inch	R134a	R22	R404A / R507	R407C		
M36-078	801 420	22	7/8	28.9	35.1	31.3	38.5	6.7	ESC
M36-118	801 421		1-1/8						

Nominal Capacities at +38°C Condensing Temperature, +4°C Evaporating Temperature (Saturated Pressures / Dew Point), 0.15 Bar Pressure Drop Between Valve Inlet and Outlet.

### Accessories and Spare Parts

#### Gasket Kit

Description	Type	Part No.
M36	KS30177-1	801268

#### Repair Kit

Description	Type	Part No.
M36 (upper assembly inc. gasket)	M36-UNF	801440