



Specifications

Model No.	Actual OD of Copper tubing (mm)	Dimension (mm)					Max Working Pressure (psig)	Burst Pressure (psig)
		A (I.D)	B (± 3)	C (± 3)	D (± 6)	E (± 1.5)		
VAS - 6 mm	6	6,4	17	168	204	13	500	2500
VAS - 8 mm	8	8,3	20	175	217.5	13	500	2500
VAS-10 mm	10	10.2	20	177.5	217.5	13	500	2500
VAS-12 mm	12	12.2	20	188.6	228.6	13	500	2500
VAS-16 mm	16	16.2	22	206.8	250.8	17	500	2500
VAS-18 mm	18	18,3	28	210	268.3	17	500	2500
VAS-22 mm	22	22.5	30	244.8	304.8	18	500	2500
VAS-28 mm	28	28.3	38	255.3	331.3	20	500	2500
VAS-35 mm	35	35.3	40	315.0	395.0	22	500	2500
VAS-42 mm	42	42,5	50	325	428.6	23	500	2500
VAS-54 mm	54	54.5	60	403.8	523.8	23	390	1950
VAS-66 mm	66	66.5	76	465.5	617.5	25	340	1700
VAS-79 mm	79	79.6	85	514.2	684.2	25	300	1500